

Electric Trolley Hoists 1000kg – 5000kg

- Specially recommended for loads over 1000kg, for transporting over long distances and/or when used frequently.
- Suitable for almost all hoists with suspension hook due to universal shackle connection.
- Travel motor with worm gear transmission ensures smooth start and self braking - a separate motor brake is not required.
- Compact, robust frame with low overall height.



All trolleys can be fitted with rubber buffers.

Model	Capacity kg	Travel speed m/min	Motor kW	Beam flange width mm	Flange thickness t max. mm	Min. curve radius m	Net weight kg
VTE1-A-18/U*	1000	18 or 18/4,5	0,18 or 0,18/0,06	58-180	19	0,90	19,5
VTE1-B-18/U*	1000	18 or 18/4,5	0,18 or 0,18/0,06	180-300	19	0,90	25,2
VTE2-A-18/U*	2000	18 or 18/4,5	0,18 or 0,18/0,06	58-180	19	1,15	26,0
VTE2-B-18/U*	2000	18 or 18/4,5	0,18 or 0,18/0,06	180-300	19	1,15	30,2
VTE3-A-11/U	3000	11 or 12/2,8	0,37 or 0,3/0,09	74-180	27	1,40	51,0
VTE3-B-18/U	3000	11 or 12/2,8	0,37 or 0,3/0,09	180-300	27	1,40	53,0
VTE5-A-11/U	5000	11 or 12/2,8	0,37 or 0,3/0,09	98-180	27	1,80	77,0
VTE5-B-11/U	5000	11 or 12/2,8	0,37 or 0,3/0,09	180-300	27	1,80	88,0
*11 or 2,8m/min travel speed on request							