

## Wire Rope Hoists up to 10,000kg



### Technical Data for Hoists

Model	Capacity in kg/ chain falls	Chain dimensions d x t in mm	Main Lift m/min	Fine Lift m/min	Hoist motor kW	Motor rating ED%	Net weight*			
							Suspension hook kg	Push trolley kg	Geared trolley kg	Electric** trolley kg
CPM 1-8	125/1	5 x 15	8	-	0,4	50	21	32	41	8
CPMF 1-8	125/1	5 x 15	8	2	0,4/0,1	33/16	24	35	44	8
CPM 1-12	160/1	5 x 15	12	-	0,4	50	21	32	41	8
CPMF 1-12	160/1	5 x 15	12	3	0,4/0,1	33/16	24	35	44	8
CPM 2-8	250/1	5 x 15	8	-	0,4	50	21	32	41	8
CPMF 2-8	250/1	5 x 15	8	2	0,4/0,1	33/16	24	35	44	8
CPM 3-6	320/2	5 x 15	6	-	0,4	50	23	34	43	8
CPMF 3-6	320/2	5 x 15	6	1,5	0,4/0,1	33/16	26	37	46	8
CPM 3-12	320/1	6 x 18	12	-	0,8	50	33	44	53	9
CPMF 3-12	320/1	6 x 18	12	3	0,8/0,2	33/16	41	52	61	9
CPM 5-4	500/2	5 x 15	4	-	0,4	50	23	34	43	8
CPMF 5-4	500/2	5 x 15	4	1	0,4/0,1	33/16 5	26	37	46	8
CPM 5-8	500/1	6 x 18	8	-	0,8	0	33	44	53	9



OneCall is a  
division of  
CraneCare



Free Phone 0800 652 4646

OneCall Solves it All  
[www.c1call.co.uk](http://www.c1call.co.uk)

Email [Sales@c1call.co.uk](mailto:Sales@c1call.co.uk)  
Fax 0121 333 3996

CPMF 5-8	500/1	6 x 18	8	2	0,8/0,2	33/16	41	52	61	9
CPM 6-6	630/2	6 x 18	6	-	0,8	50	36	47	56	9
CPMF 6-6	630/2	6 x 18	6	1,5	0,8/0,2	33/16	41	55	64	9
CPM 6-12	630/1	8 x 24	12	-	1,6	50	51	63	78	8
CPMF 6-12	630/1	8 x 24	12	3	1,6/0,4	33/16	62	80	89	8
CPM 10-4	1000/2	6 x 18	4	-	0,8	50	36	47	56	9
CPMF 10-4	1000/2	6 x 18	4	1	0,8/0,2	33/16	44	55	64	9
CPM 10-8	1000/1	8 x 24	8	-	1,6	50	51	63	78	8
CPMF 10-8	1000/1	8 x 24	8	2	1,6/0,4	33/16	62	80	89	8
CPM 12-6	1250/2	8 x 24	6	-	1,6	50	58	76	85	8
CPMF 12-6	1250/2	8 x 24	6	1,5	1,6/0,4	33/16	69	87	96	8
CPM 20-4	2000/2	8 x 24	4	-	1,6	50	58	76	85	8
CPMF 20-4	2000/2	8 x 24	4	1	1,6/0,4	33/16	69	87	96	8
* Weight for standard 3m lift. Other lifting heights on request.										
** For trolleys type A and B: Additional weight for geared trolley (VTG): 2,5kg										
*** For electric trolley (VTE) with 2 speeds 2,0kg										