









VRS Eyebolt Datasheet



Max Load Weight “G” in t for different lift combinations

Method of Lift	No. Legs	Angle of Inclination	M8	M10	M12	M16	M20	M24	M30	M36	M42	M48
	1	0	0.8	1	2	4	6	8	12	16	24	32
	2	0	1.6	2	4	8	12	16	24	32	48	64
	1	90	0.4	0.4	0.7	1.5	2.3	3.2	4.5	7	9	12
	2	90	0.8	0.8	1.5	3	4.6	6.4	9	14	18	24
	2	0-45	0.5	0.5	1	2.1	3.2	4.5	6.3	9.8	12.6	16.8
		45-60	0.4	0.4	0.7	1.5	2.3	3.2	4.5	7	9	12
	2	asymmetric	0.4	0.4	0.7	1.5	2.3	3.2	4.5	7	9	12
	3+4	0-45	0.8	0.8	1.6	3.1	4.8	6.7	9.4	14.7	18.9	25.2
		45-60	0.6	0.6	1.1	2.2	3.4	4.8	6.7	10.5	13.5	18
	3+4	asymmetric	0.4	0.4	0.7	1.5	2.3	3.2	4.5	7	9	12

Type	Nennttragf. Charge WLL	Gewicht poids weight	A	B	C	D	E	G	K	L	M	N	S	Bestellnummer réf. reference		
														VRS	VRS-F	Schlüssel
VRS-M 8	0,4 t	0,1 kg	34	11	8,5	25	25	28	47	12	8	6	15	7100554	8500911	7983986
VRS-M 10	0,4 t	0,1 kg	34	11	8,5	25	25	28	47	15	10	6	15	7982219*	7982213*	7983986
VRS-M 12	0,75 t	0,2 kg	42	13	10	30	30	34	56	18	12	8	18	7982220*	7982214*	7983987
VRS-M 16	1,5 t	0,3 kg	49	15	14	35	35	40	65	24	16	10	22	7982221**	7982215**	7983988
VRS-M 20	2,3 t	0,5 kg	57	17	16	40	40	50	75	30	20	12	27,5	7982222**	7982216**	7983989
VRS-M 24	3,2 t	0,9 kg	69	21	19	48	48	60	90	36	24	14	33	7982223**	7982217**	7983990
VRS-M 30	4,5 t	1,7 kg	86	26	24	60	60	75	112	45	30	17	41,5	7982224***	7982218***	7983991
VRS-M 36	7 t	2,9 kg	103	32	29	72	75	90	135	54	36	22	49,5	7100562	7104030	7983992
VRS-M 42	9 t	4,6 kg	120	38	34	82	85	105	158	63	42	24	58	7100563	7104031	7983993
VRS-M 48	12 t	7,0 kg	137	43	38	94	100	120	180	72	48	27	66	7100564	7104032	7983994
VRS-3/8"-16UNC	880 lbs	0,22 lbs	1 5/16"	7/16"	5/16"	1"	1"	1 1/8"	1 7/8"	3/4"	3/8"	1/4"	9/16"	7103959	7984214*	7983995
VRS-1/2"-13UNC	1650 lbs	0,44 lbs	1 5/8"	1/2"	3/8"	1 3/16"	1 3/16"	1 5/16"	2 3/16"	3/4"	1/2"	5/16"	11/16"	7103960	7984215*	7983996
VRS-5/8"-11UNC	3300 lbs	0,66 lbs	1 15/16"	9/16"	9/16"	1 3/8"	1 3/8"	1 9/16"	2 9/16"	15/16"	5/8"	3/8"	7/8"	7103961	7984216**	7983997
VRS-3/4"-10UNC	5070 lbs	1,1 lbs	2 1/4"	11/16"	11/16"	1 9/16"	1 9/16"	2"	2 15/16"	1 1/8"	3/4"	1/2"	1 1/16"	7103962	7984217**	7983998
VRS-7/8"-9UNC	5070 lbs	1,1 lbs	2 1/4"	11/16"	11/16"	1 9/16"	1 9/16"	2"	2 15/16"	1 5/16"	14/16"	1/2"	1 1/16"	7103963	7984218**	7983998
VRS-1"-8UNC	7050 lbs	2,0 lbs	2 3/4"	13/16"	13/16"	1 7/8"	1 7/8"	2 3/8"	3 9/16"	1 1/2"	1"	9/16"	1 5/16"	7103964	7984219**	7983999
VRS-1 1/4"-7UNC	9920 lbs	3,7 lbs	3 3/8"	1"	1"	2 3/8"	2 3/8"	2 15/16"	4 7/16"	1 7/8"	1 1/4"	5/8"	1 5/8"	7103965	7984220***	7984000
VRS-1 1/2"-6UNC	15430 lbs	6,4 lbs	4 1/16"	1 1/4"	1 1/4"	2 13/16"	2 15/16"	3 9/16"	5 5/16"	2 1/8"	1 1/2"	7/16"	1 15/16"	7103966	7104487	7984001
VRS-1 3/4"-5UNC	19480 lbs	10,2 lbs	4 3/4"	1 1/2"	1 1/2"	3 1/4"	3 3/8"	4 1/8"	6 1/4"	2 1/2"	1 3/4"	1"	2 1/2"	7103967	7104488	7984002
VRS-2"-4,5UNC	26450 lbs	15,4 lbs	5 3/8"	1 1/2"	1 1/2"	3 11/16"	3 15/16"	4 3/4"	7 1/16"	2 13/16"	2"	1 2/16"	5 5/8"	7103968	7104489	7984003

