

## Double Ply Polyester Webbing Sling DataSheet

### Type

Double ply webbing Sling with reinforced lifting eyes

### Technical Spec

Colour coded according to DIN-EN 1492-1  
Each 25 mm webbing width equals 1 tonne capacity










### Characteristics

Low Elongation

### Norms

According to machine directive 89/392/EC



Webbing width (mm)	Colour coded according to DIN-EN 1492-1	Working Load Limit with 1 webbing sling					Working Load Limit with 2 webbing slings			
		Straight lift	Choked lift	$\beta$			Straight lift up to 45°	Choked lift up to 45°	Straight lift 45-60°	Choked lift 45-60°
				0° -7°	7° -45°	45-60°				
										
		1,0	0,8	2,0	1,4	1,0	1,4	1,12	1,0	0,8
50	<b>WLL 1T</b>	1.000	800	2.000	1.400	1.000	1.400	1.120	1.000	800
60	<b>WLL 2T</b>	2.000	1.600	4.000	2.800	2.000	2.800	2.240	2.000	1.600
75	<b>WLL 3T</b>	3.000	2.400	6.000	4.200	3.000	4.200	3.360	3.000	2.400
100	<b>WLL 4T</b>	4.000	3.200	8.000	5.600	4.000	5.600	4.480	4.000	3.200
125	<b>WLL 5T</b>	5.000	4.000	10.000	7.000	5.000	7.000	5.600	5.000	4.000

### OneCall Lifting eye types

-  1. Flat eye
-  2. Reversed eye
-  3. Folded eye 1/2 width from 1 side
-  4. Folded eye 1/2 width from 2 sides
-  5. Folded eye 1/3 width